

F60 Specifications

Engine Type	In-Line Four Cylinder
Displacement	60.8 ci (996 cc)
Bore x Stroke	65 x 75mm (2.56 x 2.95 in)
Prop Shaft Horsepower	60hp @ 5500rpm
Compression Ratio	9.5:1
Fuel Induction	EFI (SOHC)
Exhaust	Through Propeller
Intake	Single Throttle Valve
Ignition	TCI Microcomputer
Spark Plug	DPR6EB-9
Alternator Output	17 Amp
Starting System	Electric w/PTT
Lubrication	Wet Sump
Engine Oil Capacity	2.1L/ 1.9L w/without filter
Full Throttle RPM Range	5000 ~ 6000 rpm
Cooling	Water/Thermostatic Control
Recommended Engine Oil	Yamalube® 4M (See owner's manual)
Recommended Fuel	Regular Unleaded (Minimum Pump Octane 87)
Recommended Fuel Filtration	Yamaha 10-Micron Fuel/Water Separating Filter (external)
Ethanol Blend Limit	10% Maximum
Gear Ratio	(24:13) 1.85:1
Gear Shift	F-N-R
Shaft Length	L = 20"
Degree of Tilt	69°

Degree of Trim	-4° through +20°
C.A.R.B. Rating	3-Star
Dry Weight	113kg (249 lbs)
Steering Angle (maximum)	40° from center, either direction
Warranty	3-Year Pleasure, 3-Year Government, 1-Year Commercial